
BIBTOOL

A Tool to Manipulate BibT_EX Files

C Programmer's Manual

Gerd Neugebauer

Abstract

BIBTOOL provides a library of useful C functions to manipulate BibT_EX files. This library has been used to implement the BIBTOOL program. This document describes This library and allows you to write C programs dealing with BibT_EX files.

— This documentation is still in a rudimentary form and needs additional efforts. —

This file is part of BIBTOOL Version 2.67

Copyright © 2017 Gerd Neugebauer

BIBTOOL is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 1, or (at your option) any later version.

BIBTOOL is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this documentation; see the file COPYING. If not, write to the Free Software Foundation, 675 Mass Ave, Cambridge, MA 02139, USA.

Gerd Neugebauer
Im Lerchelsbühl 5
64521 Groß-Gerau (Germany)

WWW: <http://www.gerd-neugebauer.de/>

Net: gene@gerd-neugebauer.de

Contents

1	Introduction	5
1.1	The Module <code>main.c</code>	5
2	The BibTool C Library	7
2.1	The Header File <code>bibtool/bibtool.h</code>	7
2.2	The Header File <code>bibtool/database.h</code>	7
2.3	The Module <code>database.c</code>	8
2.4	The Header File <code>bibtool/entry.h</code>	12
2.5	The Module <code>entry.c</code>	14
2.6	The Header File <code>bibtool/error.h</code>	15
2.7	The Module <code>error.c</code>	19
2.8	The Header File <code>bibtool/expand.h</code>	21
2.9	The Module <code>expand.c</code>	21
2.10	The Header File <code>bibtool/init.h</code>	21
2.11	The Module <code>init.c</code>	21
2.12	The Header File <code>bibtool/keynode.h</code>	22
2.13	The Header File <code>bibtool/key.h</code>	22
2.14	The Module <code>key.c</code>	22
2.15	The Header File <code>bibtool/macros.h</code>	27
2.16	The Module <code>macros.c</code>	28
2.17	The Header File <code>bibtool/names.h</code>	31
2.18	The Module <code>names.c</code>	32
2.19	The Header File <code>bibtool/parse.h</code>	33
2.20	The Module <code>parse.c</code>	33
2.21	The Header File <code>bibtool/print.h</code>	34
2.22	The Module <code>print.c</code>	34
2.23	The File <code>rsc.c</code>	36
2.24	The Header File <code>bibtool/pxfile.h</code>	36
2.25	The Module <code>pxfile.c</code>	36
2.26	The Header File <code>bibtool/record.h</code>	37
2.27	The Module <code>record.c</code>	41
2.28	The Header File <code>bibtool/rewrite.h</code>	43
2.29	The Module <code>rewrite.c</code>	43
2.30	The Header File <code>bibtool/resource.h</code>	45
2.31	The Header File <code>bibtool/rsc.h</code>	46
2.32	The Module <code>rsc.c</code>	46

2.33	The Header File <code>bibtool/s_parse.h</code>	47
2.34	The Module <code>s_parse.c</code>	47
2.35	The Header File <code>bibtool/stack.h</code>	49
2.36	The Module <code>stack.c</code>	49
2.37	The Header File <code>bibtool/sbuffer.h</code>	50
2.38	The Module <code>sbuffer.c</code>	50
2.39	The Header File <code>bibtool/symbols.h</code>	52
2.40	The Module <code>symbols.c</code>	54
2.41	The Header File <code>bibtool/tex_aux.h</code>	55
2.42	The Module <code>tex_aux.c</code>	55
2.43	The Header File <code>bibtool/tex_read.h</code>	56
2.44	The Module <code>tex_read.c</code>	57
2.45	The Header File <code>bibtool/type.h</code>	58
2.46	The Module <code>type.c</code>	60
2.47	The Header File <code>bibtool/version.h</code>	61
2.48	The Module <code>version.c</code>	61
2.49	The Header File <code>bibtool/wordlist.h</code>	61
2.50	The Module <code>wordlist.c</code>	62
3	Creating and Using the BibTool C Library	65
3.1	Creating the BIBTOOL C Library	65
3.2	Using the BIBTOOL C Library	65
4	Coding Standards	67
4.1	K&R-C vs. ANSI-C	67

1 Introduction

The BIBTOOL C library provides functions to deal with $\text{BIB}\text{T}_{\text{E}}\text{X}$ files. These functions are described in this document. Thus it should be fairly easy to write new C program which handle $\text{BIB}\text{T}_{\text{E}}\text{X}$ files. The reader is assumed to be familiar with $\text{BIB}\text{T}_{\text{E}}\text{X}$ files. this documentation will not repeat an introduction into $\text{BIB}\text{T}_{\text{E}}\text{X}$.

This documentation can not only be used to write new C programs dealing with $\text{BIB}\text{T}_{\text{E}}\text{X}$ files but also to understand BIBTOOL—The Program which serves as one example for using the BIBTOOLC library. In any case it is essential to understand some of the underlying concepts. Thus it is vital to read some sections very carefully.

The BIBTOOL program uses the BIBTOOL C library. Well, in fact it is the other way round. Historically the BIBTOOL program was first and then the library has been extracted from it. Nevertheless the BIBTOOL program can serve as an example how the BIBTOOL C library can be used.

1.1 The Module `main.c`

This is the BIBTOOL main module. It contains the `main()` function which evaluates the command line arguments and proceeds accordingly. This means that usually resource files and $\text{BIB}\text{T}_{\text{E}}\text{X}$ files are read and one or more $\text{BIB}\text{T}_{\text{E}}\text{X}$ files are written.

This file makes use of the BIBTOOL C library but is not part of it. For this purpose it has to provide certain functions which are expected by the library. These functions are:

```
save_input_file()
save_macro_file()
save_output_file()
```

The arguments and the expected behavior of these functions is described below.

If you are trying to understand the implementation of BIBTOOL the file `resource.h` plays a central rôle. Consult the description of this file for further details.

If you are trying to write your own program to manipulate $\text{BIB}\text{T}_{\text{E}}\text{X}$ files then this file can serve as a starting point. But you should keep in mind that this file has grown over several years and it contains the full complexity of the BIBTOOL program logic. Thus you can reduce this file drastically if you start playing around with the BIBTOOL C library.

```
int main() Function
```

```
int    argc;                Number of arguments  
char *argv[];              Array of arguments
```

This is the main function which is automatically called when the program is started. This function contains the overall program logic. It has to perform the appropriate initializations, evaluate command line arguments, and run the main loop.

Returns: 0 upon success. Usually a failure raises an exception which leads to an `exit()`. Thus this function does not need to signal an error to the calling environment.

2 The BibTool C Library

2.1 The Header File `bibtool/bibtool.h`

This header file contains includes for all other header files belonging to the BIBTOOL C library. It is here for the convenience of the C programmer who does not have to include two dozen header files but can use this single file. Thus any C program which utilizes the BIBTOOL C library can start as follows:

```
#include <bibtool/bibtool.h>
```

Note that this include file also contains includes to system specific header files. They are determined during configuration.

2.2 The Header File `bibtool/database.h`

This header file contains functions which deal with databases.

This header file provides also access to the functions and variables defined in `database.c`. Consult the documentation of this file for details.

This header file automatically includes `<stdio.h>` and `record.h` aswell.

DB

Type

This is a pointer type referencing a BibTeX database. It contains all information which characterizes a database.

The members of this record should not be used explicitly. Instead the macros should be used which are provided to access this data type.

```
typedef struct {  
    Record db_normal;           List of normal records.  
    Record db_string;          List of local macros.  
    Record db_preamble;        List of additional TeX code.  
    Record db_comment;         List of trailing comments which are not  
                                attached to records.  
    Record db_modify;          List of modification rules.  
    Record db_include;         List of included files.  
    Record db_alias;           List of aliases.  
} sDB, *DB;
```

DB NoDB		Macro
This is an invalid database. In fact it is NULL of the type DB.		
Record DBnormal()		Macro
DB	<i>The database to consider.</i>	
This is the functional representation of the normal component of a database. It can be used to extract this information. It can also be used as a lvalue.		
Record DBstring()		Macro
DB	<i>The database to consider.</i>	
This is the functional representation of the string component of a database. It can be used to extract this information. It can also be used as a lvalue.		
Record DBpreamble()		Macro
DB	<i>The database to consider.</i>	
This is the functional representation of the preamble component of a database. It can be used to extract this information. It can also be used as a lvalue.		
Record DBcomment()		Macro
DB	<i>The database to consider.</i>	
This is the functional representation of the comment component of a database. It can be used to extract this information. It can also be used as a lvalue.		
Record DBalias()		Macro
DB	<i>The database to consider.</i>	
This is the functional representation of the alias component of a database. It can be used to extract this information. It can also be used as a lvalue.		
Record DBmodify()		Macro
DB	<i>The database to consider.</i>	
This is the functional representation of the modify component of a database. It can be used to extract this information. It can also be used as a lvalue.		
Record DBinclude()		Macro
DB	<i>The database to consider.</i>	
This is the functional representation of the include component of a database. It can be used to extract this information. It can also be used as a lvalue.		

2.3 The Module database.c

This module contains functions which deal with databases. Databases are stored in an abstract datatype DB which is defined in `database.h`. Methods are provided to query and modify a database.


```
int apply_modify() Function
    DB    db;           the database
    Symbol key;         the key
    Record rec;         the record
```

Returns:

```
int * db_count() Function
    DB    db;           Database to count.
    int *lp;           pointer to an integer for the length.
```

Count all entries in a database. This includes normal as well as special records. The result is stored in a static array which is reused by `db_count()`. A pointer to this array is returned. The indices correspond to the entry types defined with `add_entry_type()` or declared as symbolic constants in `entry.h`.

The end of the array is marked by an element containing a negative number. In addition the argument `lp` can point to an integer where the number of valid elements is stored. If `lp` is NULL this step is omitted.

Returns: Static array containing the statistics.

```
Record db_find() Function
    DB    db;           Database to search in.
    Symbol key;         the key to search for
```

Search the database for a record with a given key. If `RecordOldKey` is set for the record then use this value. Otherwise use `*Heap`. `*Heap` contains the reference key of normal records.

Deleted records are ignored. An arbitrary matching record is returned. Thus if more than one record have the same key then the behavior is nondeterministic.

Returns: the record found or NULL if none is found

```
void db_forall() Function
    DB    db;           Database containing rec.
    bool (*fct)(DB,Record); Boolean valued function determining the end of the
                                processing. It takes two arguments a DB and a
                                Record.
```

Visit all normal records in the data base and apply the given function `fct` to each. If this function returns `true` then no more records need to be visited. No special order can be assumed in which the records are seen.

Returns: nothing

```
void db_insert() Function
    DB    db;           Database to insert the record into.
    Record rec;         Record to add to the database.
    bool  verbose;       Boolean to determine whether progress should be re-
                        ported.
```

Add a record to a database. The record can be any kind of record. It is added to the appropriate category.

Returns: nothing

`void db_mac_sort()` Function
 DB db; *Database to sort.*

Sort the macros of a database. The sorting uses increasing lexicographic order according to the character codes of the macro names. Note that this might lead to different results on machines with different character encodings, e.g. ASCII vs. EBCDIC.

Returns: nothing

`Symbol db_new_key()` Function
 DB db; *Database to search in.*
 Symbol key; *Key to find.*

Search the database for a record with a given old key and return the new one.

Returns: nothing

`void db_rewind()` Function
 DB db; *Database to rewind.*

Rewind the normal records of a database to point to the first record if at least one records exists. Otherwise nothing is done.

Returns: nothing

`Record db_search()` Function
 DB db; *Database to search in.*
 Symbol key; *the key to search for*

Search the database for a record with a given key. If `RecordOldKey` is set for the record then use this value. Otherwise use `*Heap`. `*Heap` contains the reference key of normal records.

Deleted records are not ignored! An arbitrary matching record is returned. Thus if more than one record have the same key then the behavior is nondeterministic.

Returns: the record found or NULL if none is found

`void db_sort()` Function
 DB db; *Database to sort.*
`int (*less)(Record,Record);` *Comparison function to use. This boolean function takes two records and returns -1 if the first one is less than the second one.*

Sort the normal records of a database. As a side effect the records are kept in sorted order in the database. The sorting order can be determined by the argument `less` which is called to compare two records.

Returns: nothing

Symbol	db_string()	Function
DB	db;	<i>Database</i>
Symbol	sym;	<i>Name of the BibTEX macro to expand.</i>
bool	localp;	<i>Boolean determining whether the search is only local to the db.</i>

Try to find the definition of a macro. First, the local values in the database `db` are considered. If this fails and `localp` is `false` then the global list is searched aswell. If all fails NULL is returned.

Returns: The macro expansion or NULL upon failure.

void	db_xref_undelete()	Function
DB	db;	<i>Database to treat</i>

Scan through the database and undelete all entries which are in the transitive closure wrt the crossref relation. Initially all not deleted entries are in the set to consider.

Returns: nothing

void	delete_record()	Function
DB	db;	<i>Database containing rec.</i>
Record	rec;	<i>Record to delete.</i>

Delete a record from a database. It is not checked, that the record really is part of the database. The record is just unlinked from its list. Just in case the record should be the first one the database record is modified.

Returns: nothing

void	free_db()	Function
DB	db;	<i>Database to release.</i>

Deallocate the memory occupied by a database. Note that any references to this database becomes invalid.

Returns: nothing

DB	new_db()	Function
----	----------	----------

Create a new database and initialize it to contain no information. If no memory is left then an error is raised and the program is terminated.

Returns: The new database.

void	print_db()	Function
FILE	*file;	<i>The file handle for printing.</i>
DB	db;	<i>The database to print</i>
char	*spec;	<i>String containing the specification of the parts to print.</i>

Print a database to a file in a way which is readable by BibTEX. The spec determines which parts should be printed and the order of this parts. The spec is processed

from left to right. Each unknown character is silently ignored. The following characters correspond to parts of the database:

- p** The preamble.
- \$** All strings (macros) contained in the database.
- S** The strings (macros) which are used in the database.
- s** The strings (macros) contained in the database where the resource `print.all.strings` determines whether all strings should be printed or the used strings only.
- n** The normal records.
- c** The comments.
- i** The includes.
- a** The aliases.
- m** The modifies.

Upper-case letters which are not mentioned are silently folded to their lower-case counterparts.

Returns: nothing

<code>bool read_db()</code>	Function
<code>DB db;</code>	<i>Database to augment.</i>
<code>String file;</code>	<i>File name to read from.</i>
<code>bool verbose;</code>	<i>Boolean to determine whether progress should be reported.</i>

Read records from a file and add them to a database. A function has to be given as one argument. This function is called for each record. If this function returns `true` then the record is added to the database. Otherwise the record is discarded.

The progress of reading is reported to `stderr` if the boolean argument `verbose` is `true`.

Returns: `true` if the file can not be opened. `false` otherwise.

2.4 The Header File `bibtool/entry.h`

This module provides also access to the functions and variables defined in `entry.c`. Consult also the documentation of this file for details.

This header file automatically includes `symbols.h`.

Symbol <code>* entry_type</code>	Variable
This is an array of strings which represent entry types. They are either built-in or user defined. Use the function <code>def_entry_type()</code> to allocate a new entry type and the function <code>get_entry_type()</code> to find a certain entry type.	

String EntryName() Macro
 Entry *Index of the entry.*
 This is the functional representation of the name component for an entry type.
 The argument is the index of an entry type. This macro can also be used as lvalue.
 No range checks are performed.

int BIB_EOF Macro
 This symbolic constant is returned when a record has to be read and the end of file
 has been encountered. It is some negative value for which no entry type is defined.

int BIB_NOOP Macro
 This symbolic constant is returned when a record has to be read and something
 has been encountered which should be ignored. It is some negative value for which
 no entry type is defined.

int BIB_STRING Macro
 This symbolic constant representing a record type of a BibTeX macro (@String).
 This is a special record type which is provided automatically.

int BIB_PREAMBLE Macro
 This symbolic constant representing a record type of a BibTeX preamble (@Preamble).
 This is a special record type which is provided automatically.

int BIB_COMMENT Macro
 This symbolic constant representing a record type of a BibTeX comment (@Comment).
 This is a special record type which is provided automatically.

int BIB_ALIAS Macro
 This symbolic constant representing a record type of a BibTeX alias (@Alias)
 which is proposed for BibTeX 1.0. This is a special record type which is provided
 automatically.

int BIB_MODIFY Macro
 This symbolic constant representing a record type of a BibTeX modification rule
 (@Modify) which is proposed for BibTeX 1.0. This is a special record type which
 is provided automatically.

int BIB_INCLUDE Macro
 This symbolic constant representing a record type of a BibTeX inclusion instruction
 (@Include) which is proposed for BibTeX 1.0. This is a special record type which
 is provided automatically.

IsSpecialRecord() Macro
 Type *Record type which should be checked.*
 Test whether a given record type denotes a special record. Special records are
 those defined above. They are provided automatically since BibTeX is supposed
 to do so as well.

Returns: TRUE iff the rcord type denoted a special record.

`IsNormalRecord()`

Macro

Type *Record type which should be checked.*

Test whether a given record is a normal record. A normal record is one defined by a user. Normal records have indices larger than those of special records.

Returns: TRUE iff the rcord type denoted a normal record.

2.5 The Module `entry.c`

This module contains functions which deal with entry types. Right from the beginning only the special record types are known. Those special record types are `@Comment`, `@Preamble`, `@String`, `@Include`, `@Modify`, and `@Alias`.

In addition to those special records the user can define additional record types which are denoted as “normal”. E.g. usually `@Article` and `@Book` are defined which are “normal” record types.

The record types are managed in this module. In the other modules only numerical representations are used. This module provides means to map those numerical ids to the string representation and back. It is also possible to define additional record types.

Part of this module is likely to be integrated into databases.

`void def_entry_type()`

Function

Symbol `sym`; *Name of the BibTeX macro to expand.*

Dynamically define an entry type. If the entry type already exists then a new printing representation is stored.

If no memory is left then an error is raised and the program is terminated

Returns: nothing

`rec_type find_entry_type()`

Function

String `s`; *String of the potential entry name.*

Look up an entry type in the array of defined entries.

Returns: The index in the array or NOOP.

Symbol `get_entry_type()`

Function

int `idx`; *Index of entry type.*

Get the printable string representation corresponding to the numerical entry type given as argument. If no entry type is defined for the given index then NULL is returned.

Returns: Print representation of the entry type or NULL.

`void init_entries()`

Function

Predefine some entry types which are stored at startup time in an array. The following entry types are predefined because they are considered special by `BIBTEX`:

BIB_STRING denotes a `BIBTEX` macro definition.

BIB_PREAMBLE denotes a preamble item which goes before the bibliography environment.

BIB_COMMENT denotes a comment entry which is passed to the output file.

BIB_ALIAS denotes an alias entry which renames an existing entry.

BIB_MODIFY denotes a modification request which alters an existing entry.

BIB_INCLUDE denotes an include request which reads in another `BIBTEX` file.

Note that this function is for internal purposes only. The normal user should call `init_bibtool()` instead.

Returns: nothing

2.6 The Header File `bibtool/error.h`

This header file provides means for issuing error messages. Most of the macros provided in this header file are based on the function `error()` described in `error.c`. Nevertheless this function covers the general cases the macros in this header file are more convenient since they hide the unnecessary arguments of the `error()` function providing appropriate values.

This header file makes available the function `error()` as defined in `error.c`.

```
int ERR_ERROR Macro
    Error type: Indicate that the error can not be suppressed and the messaged is
    marked as error.

int ERR_WARNING Macro
    Error type: Indicate that the error is in fact a warning which can be suppressed.
    The messaged is marked as warning. This flag is only in effect if the ERR_ERROR
    flag is not set.

int ERR_POINT Macro
    Error type: Indicate that the line and the error pointer should be displayed (if not
    suppressed via other flags).

int ERR_FILE Macro
    Error type: Indicate that the file name and line number should be displayed (if
    not suppressed via other flags).

int ERR_EXIT Macro
    Error type: Indicate that the error() function should be terminated by exit()
    instead of returning.
```

`void ERROR_EXIT()` Macro
 X *Error message.*
 Raise an error, print the single string argument as error message and terminate the program with `exit()`.
 Returns: nothing

`void OUT_OF_MEMORY()` Macro
 X *String denoting the type of unallocatable memory.*
 Raise an error because `malloc()` or `realloc()` failed. The argument denoted the type of memory for which the allocation failed. The program is terminated.
 Returns: nothing

`void ERROR()` Macro
 X *Error message.*
 Raise an error. Print the argument as error message and continue.
 Returns: nothing

`void ERROR2()` Macro
 X *First error message.*
 Y *Continuation of the error message.*
 Raise an error. Print the two arguments as error message and continue.
 Returns: nothing

`void ERROR3()` Macro
 X *First error message.*
 Y *Continuation of the error message.*
 Z *Second continuation of the error message.*
 Raise an error. Print the three arguments as error message and continue.
 Returns: nothing

`void WARNING()` Macro
 X *Warning message.*
 Raise a warning. Print the argument as warning message and continue.
 Returns: nothing

`void WARNING2()` Macro
 X *First warning message.*
 Y *Continuation of warning message.*
 Raise a warning. Print the two arguments as warning message and continue.
 Returns: nothing

`void WARNING3()` Macro

X *First warning message.*
Y *Continuation of warning message.*
Z *Second continuation of warning message.*

Raise a warning. Print the three arguments as warning message and continue.

Returns: nothing

`void Err()` Macro

S *String to print.*

Print a string to the error stream. This message is preceded with an indicator. The message is *not* automatically terminated by a newline.

Returns: nothing

`void ErrC()` Macro

CHAR *Character to send to output.*

Print a single character to the error stream.

Returns: nothing

`void ErrPrint()` Macro

F *String to print.*

Print a string to the error stream. The string is not preceded by any indicator not is it automatically terminated by a newline.

Returns: nothing

`void ErrPrintf()` Macro

F *Format.*

A *Argument.*

Apply a formatting instruction (with `printf()`). This macro takes a format string and a second argument which is determined by the formatting string.

Returns: nothing

`void ErrPrintf2()` Macro

F *Format*

A *First argument.*

B *Second argument.*

Apply a formatting instruction (with `printf()`). This macro takes a format string and two additional arguments which are determined by the formatting string.

Returns: nothing

`void ErrPrintf3()` Macro

F *Format*

A *First argument.*

B *Second argument.*

C *Third argument.*

Apply a formatting instruction (with `printf()`). This macro takes a format string and three additional arguments which are determined by the formatting string.

Returns: nothing

`void FlushErr` Macro

Flush the error stream. This can be useful when single characters are written to an error stream which does buffering.

`void VerbosePrint1()` Macro

A *Verbose message.*

Print an informative message to the error stream.

Returns: nothing

`void VerbosePrint2()` Macro

A *Verbose message.*

B *Continuation of verbose message.*

Print an informative message consisting of two substrings to the error stream.

Returns: nothing

`void VerbosePrint3()` Macro

A *Verbose message.*

B *Continuation of verbose message.*

C *Second continuation of verbose message.*

Print an informative message consisting of three substrings to the error stream.

Returns: nothing

`void VerbosePrint4()` Macro

A *Verbose message.*

B *Continuation of verbose message.*

C *Second continuation of verbose message.*

D *Third continuation of verbose message.*

Print an informative message consisting of four substrings to the error stream.

Returns: nothing

`void DebugPrint1()` Macro

A *Debug message.*

This Macro is for debugging purposes. The compilation determines whether this macro prints its argument or simply ignores it. This is achieved by defining or undefining the macro `DEBUG` when compiling.

Returns: nothing

`void DebugPrint2()` Macro

A *Debug message.*

B *Continuation of the debug message.*

This Macro is for debugging purposes. The compilation determines whether this macro prints its arguments or simply ignores them. This is achieved by defining or undefining the macro `DEBUG` when compiling.

Returns: nothing

```
void DebugPrint3() Macro
    A                Debug message.
    B                Continuation of the debug message.
    C                Second continuation of the debug message.
```

This Macro is for debugging purposes. The compilation determines whether this macro prints its arguments or simply ignores them. This is achieved by defining or undefining the macro `DEBUG` when compiling.

Returns: nothing

```
void DebugPrintF1() Macro
    A                Debug message.
```

This Macro is for debugging purposes. The compilation determines whether this macro prints its argument or simply ignores it. This is achieved by defining or undefining the macro `DEBUG` when compiling.

Returns: nothing

```
void DebugPrintF2() Macro
    F                The format for the debug message.
    A                Debug message.
```

This Macro is for debugging purposes. The compilation determines whether this macro prints its arguments or simply ignores them. This is achieved by defining or undefining the macro `DEBUG` when compiling.

Returns: nothing

```
void DebugPrintF3() Macro
    F                The format for the debug message.
    A                Debug message.
    B                Continuation of the debug message.
```

This Macro is for debugging purposes. The compilation determines whether this macro prints its arguments or simply ignores them. This is achieved by defining or undefining the macro `DEBUG` when compiling.

Returns: nothing

2.7 The Module `error.c`

To ensure a consistent appearance of error messages `BIBTOOL` provides one generic error reporting routine. This routine is controlled by several arguments to allow maximum

flexibility.

Usually it is awkward to fill out all those arguments. To avoid this trouble the header file `error.h` provides some macros which cover the most common situation and hide unnecessary details.

<code>void error()</code>	Function
<code>int type;</code>	<i>Error type: boolean combination of the error bits as defined in <code>error.h</code>.</i>
<code>String s1;</code>	<i>1st error message or NULL.</i>
<code>String s2;</code>	<i>2nd error message or NULL.</i>
<code>String s3;</code>	<i>3rd error message or NULL.</i>
<code>String line;</code>	<i>Current line when error occurred (for reading errors).</i>
<code>String err_pos;</code>	<i>Error position in line <code>line</code>.</i>
<code>int line_no;</code>	<i>The line number where the error occurred.</i>
<code>char * fname;</code>	<i>The file name where the error occurred.</i>

This is the generic error printing routine. It prints an error message together with an optional filename, the line number, the errorous line and a pointer to the problematic position.

All parts of an error message are optional and can be suppressed under certain conditions. The error type determines which parts are actually shown. It is a boolean combination of the following flags which are defined in `error.h`:

ERR_ERROR If this bit is set then the error message is marked as “error”. The flag `ERR_WARNING` is ignored in this case. This kind of messages can not be suppressed.

ERR_WARNING If this bit is set and `ERR_ERROR` is not set then the error message is marked as “warning”. `ERR_WARNING` is ignored in this case.

ERR_POINT If this bit is set then the line `line` is shown together with a pointer to the byte pointed to by `err_pos`. Otherwise the line is not shown.

ERR_FILE If this bit is set then the name of the file `file_name` and the line number `lineno` are shown. Otherwise the file name and the line number are suppressed.

ERR_EXIT If this bit is set then the error routine calls `exit(-1)` at the end. This implicitly sets the `ERR_ERROR` bit as well.

The error message itself can be split in up to three strings `s1`, `s2`, and `s3`. Those strings are concatenated. They can also be `NULL` in which case they are ignored.

The error message is written to the stream determined by the variable `err_file`. This variable refers to the `stderr` stream initially but can be redirected to any other destination.

Returns: nothing

<code>void init_error()</code>	Function
--------------------------------	----------

`FILE * file;` *the output file to write error messages to*

Initialize the error reporting.

Returns: nothing

2.8 The Header File `bibtool/expand.h`

This header file makes available the function defined in `expand.c`. This file includes the header file `database.h`.

2.9 The Module `expand.c`

This module contains functions to expand macros as they are appearing in right hand sides of equations. This can be used to get rid of additional macro definitions.

Symbol	expand_rhs()	Function
<code>Symbol sym;</code>		<i>Name of the $\text{BIB}T_{EX}$ macro to expand.</i>
<code>Symbol pre;</code>		<i>This is the opening brace character to be used. For $\text{BIB}T_{EX}$ the valid values are { or ". This value has to match to post.</i>
<code>Symbol post;</code>		<i>This is the closing brace character to be used. For $\text{BIB}T_{EX}$ the valid values are } or ". This value has to match to pre.</i>
<code>DB db;</code>		<i>Database containing the macros.</i>
<code>bool lowercase;</code>		

Expand the right hand side of an item. Each macro which is defined in this database is replaced by its value. The result is kept in a static variable until the next invocation of this function overwrites it.

Returns: A pointer to the expanded string. This value is kept in a static variable of this function and will be overwritten with the next invocation.

2.10 The Header File `bibtool/init.h`

This header file provides the prototype for the global initialization function which is required to be called before any action can be performed.

2.11 The Module `init.c`

This module contains the global initialization function which has to be called before any modules in `BIBTOOL` are activated. This is for convenience, thus nobody has to call the

various initialization functions for the different modules by hand.

<code>void init_bibtool()</code>	Function
<code>char * progame;</code>	<i>Name of the program for KPATHSEA.</i>
Perform any initializations necessary for BIBTOOL.	
Returns: nothing	

2.12 The Header File `bibtool/keynode.h`

This header file provides the datatype of a keynode. This is an internal structure which is used to built parse trees from format specifications. Usually this is done in `key.c` and should not be visible outside.

KeyNode	Type
----------------	------

```
typedef struct kEYnODE {
    short int      kn_type;
    short int      kn_pre;
    short int      kn_post;
    Symbol          kn_symbol;
    String          kn_from;
    String          kn_to;
    struct kEYnODE *kn_next;
    struct kEYnODE *kn_then;
    struct kEYnODE *kn_else;
} *KeyNode, SKeyNode;
```

2.13 The Header File `bibtool/key.h`

This header file provides functions to deal with keys as they are defined in `keys.h`.

This header file automaticall includes the header files `database.h` and `sbuffer.h` since datatypes defined there are required.

2.14 The Module `key.c`

<code>void add_format()</code>	Function
<code>char *s;</code>	<i>Specification string</i>
Add a key format specification to the current specification. This specification is used for generating new reference keys. Thus the resource <code>rsc_make_key</code> is turned	

on aswell.

Several strings are treated special. If a special format is encountered then the effect is that the old key specification is cleared first before the new format is added:

empty The empty format is activated. This means that the format is cleared and without further action the default key will be used.

long The long format is activated. This means that authors names with initials and the first word of the title are used.

short The short format is activated. This means that authors last names and the first word of the title are used.

new.long This means that the long format will be used but only if the record does not have a key already.

new.short This means that the short format will be used but only if the record does not have a key already.

Returns: nothing

```
void add_ignored_word() Function
    Symbol word; Word to add.
```

Add a new word to the list of ignored words for title key generation. The argument has to be saved by the caller! This means that it is assumed that the argument is a symbol.

Returns: nothing

```
void add_sort_format() Function
    char *s; Specification string
```

Add a sort key format specification to the current specification. This specification is used for generating new sort keys.

Several strings are treated special. If a special format is encountered then the effect is that the old key specification is cleared first before the new format is added:

empty The empty format is activated. This means that the format is cleared and without further action the default key will be used.

long The long format is activated. This means that authors names with initials and the first word of the title are used.

short The short format is activated. This means that authors last names and the first word of the title are used.

new.long This means that the long format will be used but only if the record does not have a key already.

new.short This means that the short format will be used but only if the record does not have a key already.

Returns: nothing

`int apply_fmt()` Function

StringBuffer *sb; *Destination string buffer.*
char * fmt; *Format specification,*
Record rec; *Record to consider.*
DB db; *Database containing rec.*

Expands an arbitrary format specification for a given record. The format specification is given as a string. The result is stored in a string buffer.

Returns: 1 iff the format is invalid or the evaluation fails. 0 otherwise.

`void clear_ignored_words()` Function

Delete the list of ignored words. Afterwards no words are recognized as ignored words.

Returns: nothing

`void def_format_type()` Function

String s;

Returns: nothing

`void end_key_gen()` Function

Finalize the key generation. Any previously recorded keys are discarded.

Returns: nothing

`String fmt_expand()` Function

StringBuffer *sb; *destination string buffer*
Uchar * cp; *format*
DB db; *Database containing rec.*
Record rec; *Record to consider.*

Expands a format specification of the string buffer.

Returns: The first character after the

`bool foreach_ignored_word()` Function

bool (*fct)(Symbol); *Function to apply.*

Iterator a given function `fct` is applied to each ignored word in turn. If the function returns 0 then the loop is terminated. The different words are visited in a fixed order which does not necessarily coincide with the natural order of words. Thus don't assume this.

Returns: The return status of the last `fct` call.

`void free_key_node()` Function

KeyNode kn; *KeyNode to be freed.*

A tree rooted at a given KeyNode will be freed.

Returns: nothing

String `get_base()`

Function

Getter for the printable representation of the `key_base`.

Returns:

Symbol `get_field()`

Function

DB `db`;

Database containing `rec`.

Record `rec`;

Record to analyze.

Symbol `name`;

Field name to search for. This has to be a symbol if a normal field is sought. For pseudo fields it can be an arbitrary string.

Evaluate the record `rec`. If name starts with `@` then check the record name. If name starts with `$` then return the special info. Else search in Record `rec` for the field name and return its value. `NULL` is returned to indicate failure.

Returns: The address of the value or `NULL`.

Symbol `get_separator()`

Function

int `n`;

the index

Getter for the key separator. The elements under the index have the following meaning:

- 0** The default key which is used when the formatting instruction fails completely.
- 1** The separator which is inserted between different names of a multi-authored publication.
- 2** The separator inserted between the first name and the last name when a name is formatted.
- 3** The separator inserted between the last names when more then one last name is present
- 4** The separator between the name and the title of a publication.
- 5** The separator inserted between words of the title.
- 6** The separator inserted before the number which might be added to disambiguate reference keys.
- 7** The string which is added when a list of names is truncated. (`.ea`)

Returns: the separator for the given index or `NULL`

void `make_key()`

Function

DB `db`;

Database containing the record.

Record `rec`;

Record to consider.

Generate a key for a given record.

Returns: nothing

`void make_sort_key()` Function
 DB db; *Database containing the record.*
 Record rec; *Record to consider.*
 Returns: nothing

`bool mark_key()` Function
 DB db; *Database containing the record.*
 Record rec; *Record to consider*
 Set the key mark for the key symbol of a record.
 Returns: nothing

`void set_base()` Function
 String value; *String representation of the new value.*
 Define the key base. This value determines the format of the disambiguation string added to a key if required. The following values are considered:

- If the value is **upper** or starts with an upper case letter then the disambiguation is done with upper-case letters.
- If the value is **lower** or starts with a lower case letter then the disambiguation is done with lower-case letters.
- If the value is **digit** or starts with an digit then the disambiguation is done with arabic numbers.

The comparison of the keywords is done case insensitive. The special values take precedence before the first character rules.

If an invalid value is given to this function then an error is raised and the program is terminated.

Returns: nothing

`bool set_field()` Function
 DB db; *Database containing rec.*
 Record rec; *Record to receive the value.*
 Symbol name; *Field name to add.*
 Symbol value; *the new value*

Store the given field or pseudo-field in a record. If the field is present then the old value is overwritten. Otherwise a new field is added. Fields starting with a \$ or @ are treated special. They denote pseudo fields. If such a pseudo field is undefined then the assignment simply fails.

In contrast to the function `push_to_record()` this function does not assume that the arguments are symbols. In addition to `push_to_record()` it also handles pseudo-fields.

Returns: **false** if the assignment has succeeded.

`void set_separator()` Function

`int n;` *Array index to modify.*
`String s;` *New value for the given separator. The new value is stored as a symbol. Thus the memory of `s` need not to be preserved after this function is completed. The characters which are not allowed are silently suppressed.*

Modify the `key_seps` array. This array contains the different separators used during key formatting. The elements of the array have the following meaning:

- 0** The default key which is used when the formatting instruction fails completely.
- 1** The separator which is inserted between different names of a multi-authored publication.
- 2** The separator inserted between the first name and the last name when a name is formatted.
- 3** The separator inserted between the last names when more then one last name is present
- 4** The separator between the name and the title of a publication.
- 5** The separator inserted between words of the title.
- 6** The separator inserted before the number which might be added to disambiguate reference keys.
- 7** The string which is added when a list of names is truncated. (`.ea`)

Returns: nothing

`void start_key_gen()` Function

Start the key generation. Any recorded keys are discarded.

Returns: nothing

2.15 The Header File `bibtool/macros.h`

This header file contains definitions for the `Macro` structure. `Macro` is the pointer type corresponding to the structure `SMacro`. All C macros and functions provided through this header file deal with the pointer type. The structure itself is used in the allocation function only.

Macro Type

This is a pointer type to represent a mapping from a string to another string. This mapping is accompanied by a counter which can be used as a reference count.

```
typedef struct mACRO {
```

```

Symbol      mc_name;      Name of the macro.
Symbol      mc_value;     Value of the macro.
int          mc_used;      Reference count.
struct mACRO *mc_next;     Pointer the next macro.
} SMacro, *Macro;

```

Macro MacroNULL

Macro

This is the NULL pointer for the Macro type. It can be used as a special or illegal macro.

String MacroName()

Macro

M *Macro to consider*

This is the functional representation of the name component of a Macro. It can be used to extract this information. It can also be used as a lvalue.

String MacroValue()

Macro

M *Macro to consider*

This is the functional representation of the value component of a Macro. It can be used to extract this information. It can also be used as a lvalue.

int MacroCount()

Macro

M *Macro to consider*

This is the functional representation of the counter component of a Macro. It can be used to extract this information. It can also be used as a lvalue.

Macro NextMacro()

Macro

M *Macro to consider*

This is the functional representation of the next Macro. It can be used to extract this information. It can also be used as a lvalue.

2.16 The Module macros.c

void def_field_type()

Function

String s; *String containing an equation. This string is modified during the process.*

This function adds a printing representation for a field name to the used list. The argument is an equation of the following form

type = value

type is translated to lower case and compared against the internal representation. *value* is printed at the appropriate places instead.

Returns: nothing

int def_macro() Function

Symbol name; *name of the macro.*
 Symbol val; *NULL or the value of the new macro*
 int count; *initial count for the macro.*
 Define or undefine a macro.
 Returns: nothing

void dump_mac() Function

char *fname; *File name of the target file.*
 int allp; *if == 0 only the used macros are written.*
 Write macros to a file.
 Returns: nothing

bool each_macro() Function

Macro *m; the macro to start with*
 bool (*fct) (Symbol ,Symbol);
 Iterate over a linked list of macros. A function is applied to each macro found.
 The loop terminates if the function returns **false**.
 Returns: **true** if the function has terminated the loop and **false** in case the end
 of the list has been reached

void foreach_macro() Function

bool (*fct) (Symbol ,Symbol);
 Apply a function to each macro in turn. The function is called with the name and
 the value of the macro. If it returns **false** then the processing of further macros
 is suppressed.
 The function given as argument is called with two string arguments. The first is
 the name of the macro and the second is its value. Both are symbols and must not
 be modified in any way.
 The order of the enumeration of the macros is determined by the implementation.
 No specific assumptions should be made about this order.
 Returns: nothing

void free_macro() Function

Macro mac; *First Macro to release.*
 Free a list of macros. The memory allocated for the Macro given as argument and
 all structures reachable via the NextMacro pointer are released.
 Returns: nothing

Symbol get_item() Function

<code>Symbol name;</code>	<i>Symbol to get the print representation for.</i>
<code>int type;</code>	<i>One of the values <code>SYMBOL_TYPE_UPPER</code>, <code>SYMBOL_TYPE_LOWER</code>, or <code>SYMBOL_TYPE_CASED</code> as they are defined in <code>type.h</code>.</i>

Return the print representation of a `BIBTEX` string. The appearance is determined by the `items` mapping. If no appropriate entry is found then `type` is used to decide whether the item should be returned as upper-case, lower-case or first upper only.

Returns: A pointer to a static string. This location is reused upon the next invocation of this function.

<code>Symbol get_key()</code>	Function
<code>Symbol name;</code>	<i>the name of the key to find. This must be in lower-case</i>

Get the printable representation of a key. If a special representation has been registered then this representation is returned. Otherwise the (lower-case) key is returned.

Returns: the requested representation

<code>void init_macros()</code>	Function
Initialize some macros from a table defined in the configuration file or given as define to the C compiler. This function has to be called to initialize the global macros.	

Note that this function is for internal purposes only. The normal user should call `init_bibttool()` instead.

Returns: nothing

<code>Symbol look_macro()</code>	Function
<code>Symbol name;</code>	<i>The name of the macros to find. This needs not to be a symbol.</i>
<code>int add;</code>	<i>Initial reference count or indicator that no new macro is required.</i>

Return the value of a macro if it is defined. This value is a symbol. If the macro is undefined then `NULL` is returned. In this case the value of `add` determines whether or not the macro should be defined. If it is less than 0 then no new macros is defined. Otherwise a new macro is defined. The value is the empty string and the initial reference count is `add`.

Returns: The value or `NULL`.

<code>Macro new_macro()</code>	Function
<code>Symbol name;</code>	<i>Name of the macro. This must be a symbol.</i>
<code>Symbol value;</code>	<i>The value of the macro. This must be a symbol.</i>
<code>int count;</code>	<i>The initial reference count.</i>
<code>Macro next;</code>	<i>The next pointer of the <code>Macro</code> structure.</i>

Allocate a new macro structure and fill it with initial values. Upon failure an error

is raised and `exit()` is called.

Returns: The new Macro.

<code>void save_key()</code>		Function
Symbol name;	<i>the name of the key in lower</i>	
Symbol key;	<i>the key as printed</i>	
Save a mapping of a lower-case key to a printed representation.		
Returns: nothing		

2.17 The Header File `bibtool/names.h`

SNameNode	Type
------------------	------

The name format is translated internally into a list of nodes which are easier to evaluate since they avoid the reparsing of the format. This structure contains such a node.

```
typedef struct nameNODE {
    int          nn_type;
    int          nn_strip;
    int          nn_trim;
    Symbol       nn_pre;
    Symbol       nn_mid;
    Symbol       nn_post;
    struct nameNODE *nn_next; Pointer to the next name node
} SNameNode, *NameNode;
```

<code>NameNode NameNULL</code>	Macro
--------------------------------	-------

The NULL pointer to a `NameNode` which can be used as a special value to indicate the end of a `NameNode` list.

<code>int NameType()</code>	Macro
NN	<i>the name node</i>
Returns:	

<code>int NameStrip()</code>	Macro
NN	<i>the name node</i>
Returns:	

<code>int NameTrim()</code>	Macro
NN	<i>the name node</i>
Returns:	

String NamePre()		Macro
NN	<i>the name node</i>	
Returns:		
String NameMid()		Macro
NN	<i>the name node</i>	
Returns:		
String NamePost()		Macro
NN	<i>the name node</i>	
Returns:		
NameNode NextName()		Macro
NN	<i>NameNode to consider.</i>	
	Functional representation of the pointer to the next NameNode .	
Returns:	The next NameNode .	

2.18 The Module `names.c`

NameNode name_format()		Function
String s;		
Returns:		
String pp_list_of_names()		Function
String * wa;	<i>Word array of name constituents</i>	
NameNode format;	<i>the format of the name</i>	
String trans;	<i>the translation table</i>	
int max;	<i>the limit for the number of names to be formatted</i>	
String comma;	<i>","</i>	
String and;	<i>name separator</i>	
char * namesep;		
char * etal;		
Pretty-print a list of names.		
Returns:	Pointer to static string which is reused upon the next invocation of this function.	
void pp_one_name()		Function
Returns:	nothing	


```
void set_name_format() Function
    NameNode *nodep;
    char *      s;

    Returns: nothing
```

2.19 The Header File bibtool/parse.h

This header file contains functions which deal with the parsing of BibTeX files. They are defined in `parse.c` and declared in this file.

2.20 The Module parse.c

```
void init_read() Function
    Initialize the reading apparatus. Primarily try to figure out the file search path.

    Note that this function is for internal purposes mainly. The normal user should
    call init_bibtex() instead. Just in case the search paths are changed afterwards
    this function has to be called again to propagate the information.

    Returns: nothing
```

```
int parse_bib() Function
    Record rec; Record to store the result in.

    Read one entry and fill the internal record structure. Return the type of the entry
    read.

    BIB_EOF is returned if nothing could be read and the end of the file has been
    encountered.

    BIB_NOOP is returned when an error has occurred. This is an indicator that no
    record has been read but the error recovery is ready to try it again.

    This function is for internal purposes mainly. See read_db() for a higher level
    function to read a database.

    Returns: The type of the entry read, BIB_EOF, or BIB_NOOP.
```

```
bool read_rsc() Function
    String name; Name of the file to read from.

    Read a resource file and evaluate all instructions contained.

    The characters #, %, and ; start an endline comment but only between resource
    instructions. They are not recognized between a resource instruction and its value
    or inside the value braces.

    This function is contained in this module because it shares several functions with
    the BibTeX parsing routines.
```

Returns: `true` if an error has occurred

`bool see_bib()`

Function

`String fname;` *Name of the file or NULL.*

Open a BIB_TE_X file to read from. If the argument is `NULL` then `stdin` is used as input stream.

This function has to be called before `parse()` can be called. It initializes the parser routine and takes care that the next reading is done from the given file.

The file opened with this function has to be closed with `seen()`.

This function is for internal purposes mainly. See `read_db()` for a higher level function to read a database.

Returns: `true` iff the file could be opened for reading.

`bool seen()`

Function

Close input file for the BIB_TE_X reading apparatus. After this function has been called `parse()` might not return sensible results.

This function is for internal purposes mainly. See `read_db()` for a higher level function to read a database.

Returns: `false` if an attempt was made to close an already closed file.

`void set_rsc_path()`

Function

`String val;` *The string representation of the file search path.*

Initialize the resource file reading apparatus. Primarily try to figure out the file search path.

Returns: nothing

2.21 The Header File `bibtool/print.h`

This header file provides access to the functions and variables defined in `print.c`. Consult also the documentation of this file for details.

This header file automatically includes `record.h` and `database.h`.

2.22 The Module `print.c`

This module provides also access to the functions and variables defined in `entry.c`. Consult also the documentation of this file for details.

`void fput_record()`

Function

FILE * file;	<i>Stream to print onto.</i>
DB db;	<i>Database containing the record.</i>
Record rec;	<i>Record to print.</i>
String start;	<i>Initial string used before the type. Should be "@" normally.</i>

Format and print a complete record onto a given stream. for further details see `put_record()`.

Returns: nothing

String get_symbol_type()	Function
Getter for the symbol type.	

Returns: one of the values `SYMBOL_TYPE_UPPER`, `SYMBOL_TYPE_LOWER`, or `SYMBOL_TYPE_CASED` as defined in header `type.h`

void put_record()	Function
int (* fct)(int);	<i>function to use for writing a character.</i>
Record rec;	<i>Record to print.</i>
DB db;	<i>Database containing the record.</i>
String start;	<i>Initial string used before the type. Should be "@" normally.</i>

Format and print a complete record. The record type and several resources are taken into account. The following external variables (from `rsc.c`) are taken into account:

rsc_parentheses If this boolean variable is `true` then (and) are used to delimit the record. Otherwise { and } are used.

rsc_col_p This integer variable controls the indentation of preamble records.

rsc_col_s This integer variable controls the indentation of string records.

rsc_expand_macros If this boolean variable is set then macros are expanded before the record is printed. This does not effect the internal representation.

rsc_col This integer variable controls the indentation of normal records.

rsc_col_key This integer variable controls the indentation of the key in a normal record.

rsc_newlines This integer variable controls the number of newlines printed after a normal record.

rsc_linelen This integer variable controls the length of the line. The line breaking algorithm is applied if this column is about to be violated.

rsc_indent This integer variable controls the indentation of equations.

rsc_eq_right This boolean variable controls the alignment of the = in equations. If it is set then the equality sign is flushed right. Otherwise it is flushed left.

The field in the record are sorted with `sort_record()` before they are printed.

In normal records all fields not starting with an allowed character are ignored. Thus it is possible to store private and invisible information in a field. Simply start the field name with an not allowed character like %.

Returns: nothing

```
void set_symbol_type() Function
String s; String description of the value.
```

Function to set the symbol type which is used by the printing routine. The argument is a string describing the value to use. Possible values are "upper", "lower", and "cased". The comparison of the values is performed case insensitive.

If no appropriate value is found then an error message is issued as the only action.

This function is called from

2.23 The File rsc.c

Returns: nothing

```
char * sput_record() Function
DB db; Database containing the record.
Record rec; Record to print.
String start; Initial string used before the type. Should be "@" normally.
```

Format and print a complete record into a string and return it. The string returned points to static memory which is reused upon the next invocation of this function.

Returns: The string containing the printed representation.

2.24 The Header File bibtool/pxfile.h

This module provides access to the functions and variables defined in pxfile.c. Consult also the documentation of this file for details.

This header file automatically includes bibtool.h and <stdio.h>.

2.25 The Module pxfile.c

This file provides routines for extended file opening. Files are sought in a list of directories and optionally with a set of extensions appended to them.

Patterns may be given which are used to determine the full file name. The patterns are stored in a special data structure. A function is provided to allocate a pattern structure and fill it from a string specification.

px_filename

Variable

This variable contains the file name actually used by the last `px_fopen()` call. The memory is automatically managed and will be reused by the next call to `px_fopen()`. Thus if you need to use it make a private copy immediately after the call to the function `px_fopen()`.

FILE * px_fopen()

Function

`char * name;` *(base) name of the file to open.*
`char * mode;` *Mode for opening the file like used with `fopen()`.*
`char **pattern;` *A NULL terminated array of patterns.*
`char **path;` *The NULL terminated array of directories.*
`int (* show)(char*);` *A function pointer or NULL.*

Open a file using path and pattern.

Returns: A file pointer referring to the file or NULL.

char ** px_s2p()

Function

`char * s;` *String to analyze*
`int sep;` *Separator*

Translate a path string specification into an array of the components. The memory of the array is malloced and should be freed when not used any longer.

Returns: The array of the components

2.26 The Header File `bibtool/record.h`

This module contains functions which deal with records in databases.

Record

Type

This data type represents a record in a `BIBTEX` database. Since the record can contain an arbitrary number of fields the central rôle is taken by the dynamic array `rc_heap`. This array contains at even positions the name of the field and the following odd position the associated value. In normal records the position 0 contains the reference key of the record.

If a field is deleted then the name is replaced by a NULL. The structure member `rc_free` contains the size of the heap.

The type of the record is determined by the integer `rc_type`.

```
typedef struct rECORD {
```

Symbol	<code>rc_key;</code>	<i>The sort key.</i>
Symbol	<code>rc_old_key;</code>	<i>The old sort key.</i>
<code>rec_type</code>	<code>rc_type;</code>	<i>The type of the record.</i>
<code>int</code>	<code>rc_flags;</code>	<i>Some bits; e.g. used during selecting aux records.</i>
<code>int</code>	<code>rc_free;</code>	<i>The size of the heap. This is purely internal and must not be modified.</i>
Symbol *	<code>rc_heap;</code>	<i>The heap.</i>
Symbol	<code>rc_comment;</code>	<i>The comment following the given record.</i>
Symbol	<code>rc_source;</code>	<i>The source of the record. I.e. the file name it has been read from.</i>
	<code>struct rECORD *rc_next;</code>	<i>Pointer to the next record.</i>
	<code>struct rECORD *rc_prev;</code>	<i>Pointer to the previous record.</i>

} **SRecord, *Record;**

Record RecordNULL Macro
 Symbolic constant for the NULL pointer of type **Record**. This is used as special (invalid) record.

rec_type RecordType() Macro
R *Record to consider.*

Functional representation of the record token. This can be used to access the token component of a record. It can also be used as lvalue.

Returns: The pure token.

int RecordFlags() Macro
R *Record to consider.*

Functional representation of the record type. This can be used to access the token component of a record. It can also be used as lvalue.

Returns: The flags as integer.

int RecordFlagMARKED Macro
 Bit mask for the **MARKED** flag of a record. The mark is used temporarily to determine certain records; e.g. during gc.

This macro is usually not used directly but implicitly with other macros from this header file.

int RecordFlagXREF Macro
 Bit mask for the **XREF** flag of a record. This flag is maintained to indicate that the record contains an **crossref** field. This is done for efficiency reasons only.

This macro is usually not used directly but implicitly with other macros from this header file.

int RecordFlagDELETED Macro

Bit mask for the `DELETED` flag of a record. This flag indicates that the record has been deleted. To avoid dangling pointers the deleted records are not removed from the database immediately but a call to `record_gc()` performs this cleanup. In the meantime the deleted records are just left in the chain. Many operations automatically ignore deleted records.

This macro is usually not used directly but implicitly with other macros from this header file.

`int SetRecordXREF()` Macro

R *The record to consider.*

Mark the record with the `XREF` flag. If it is marked already nothing is done.

The `XREF` flag is used to mark those records which contain a `crossref` field. This is done for efficiency only.

Returns: The new value of the record flags.

`int ClearRecordXREF()` Macro

R *The record to consider.*

Remove the `XREF` mark.

Returns: The new value of the record flags.

`int RecordIsXREF()` Macro

R *Record to consider.*

Check whether the `XREF` flag of a record is set.

Returns: `FALSE` iff the `XREF` flag is not set.

`int SetRecordDELETED()` Macro

R *Record to consider.*

Mark the record with the `DELETED` flag. If it is marked already nothing is done.

The `DELETED` flag is used to mark those records which should be treated as non existent. Deleted records are ignored for most operations.

Returns: The new value of the record flags.

`int ClearRecordDELETED()` Macro

R *Record to consider.*

Remove the deleted flag. Thus you can effectively undelete a record as long as its memory has not been released.

Returns: The new value of the record flags.

`int RecordIsDELETED()` Macro

R *Record to consider.*

Check whether the record is marked as deleted.

Returns: FALSE iff the DELETED flag is not set.

int SetRecordMARK() Macro

R *Record to consider.*

Mark the record. The mark is used temporarily. Do not assume that the mark is preserved in each function.

Returns: The new value of the record flags.

int ClearRecordMARK() Macro

R *Record to consider.*

Remove the deleted flag. Thus you can effectively undelete a record as long as its memory has not been released.

Returns: The new value of the record flags.

int RecordIsMARKED() Macro

R *Record to consider.*

Check whether the record is marked as deleted.

Returns: FALSE iff the DELETED flag is not set.

String RecordOldKey() Macro

R *Record to consider*

String RecordSortkey() Macro

R *Record to consider.*

This is the functional representation of the sort key of a record. This can be used to access the key component of a record. It can also be used as lvalue.

Note that the reference key of a normal record is stored in the heap at position 0.

String * RecordHeap() Macro

R *Record to consider.*

The heap of a record is a array of strings. The even positions contain the names of fields and the following array cell contains its value. If the name or value is NULL then this slot is not used. Thus it is easy to delete a field. Simply write a NULL into the appropriate place.

Record NextRecord() Macro

R *Record to consider*

This is the functional representation of the next record of a record. It can be used to get this value as well as an lvalue to set it.

Record PrevRecord() Macro

R *Record to consider*

This is the functional representation of the previous record of a record. It can be used to get this value as well as an lvalue to set it.

String RecordComment() Macro
 R *Record to consider*

This is the functional representation of the comment component of a record. It can be used to get this value as well as an lvalue to set it.

String RecordSource() Macro
 R *Record to consider*

This is the functional representation of the source indicator of a record. It is a string containing the file name from which this record has been read. The empty string is used to denote unknown sources.

Returns:

int RecordFlags() Macro
 R *Record to consider*

This is the functional representation of the record flags. They are extra bits used for arbitrary purposes. Right now only the bit with the mask 1 is used for selecting the records found in an aux file.

Returns:

2.27 The Module record.c

void add_sort_order() Function
 Symbol val; *string resource of the order.*
 Insert the sort order into the order list.
 Returns: nothing

Record copy_record() Function
 Record rec; *The record to copy.*
 Copy a record and return a new instance. If no memory is left then an error is raised and the program is terminated.
 Returns: The new copy of **rec**.

int count_record() Function
 Record rec; *the record*
 Returns:

void free_1_record() Function
 Record rec; *record to free*
 Free the memory occupied by a single record. This does not ensure that there is no dangling pointer to the record. Thus beware!
 Returns: nothing

- void free_record()** Function
 Record rec; *Arbitrary Record in the chain.*
 Release a list of records. All records reachable through a previous/next chain are deallocated.
 Returns: nothing
- Record new_record()** Function
 int token; *The token type of the record.*
 int size; *The initial heap size.*
 Create a new record and return it. If no memory is left then an error is raised and the program is terminated.
 Returns: The new record.
- WordList new_wordlist()** Function
 Symbol s; *Initial string to fill in the WordList structure*
 Allocate a WordList and fill its slots.
 Returns:
- void provide_to_record()** Function
 Record rec; *the record*
 Symbol s; *Left hand side of the equation.*
 Symbol t; *Right hand side of the equation.*
 Put an equation s=t onto the heap of a record if the key s is not defined already. If a field s is already there then the value is ignored. The arguments are expected to be symbols. Thus it is not necessary to make private copies and it is possible to avoid expensive string comparisons.
 Returns: nothing
- void push_to_record()** Function
 Record rec; *the record*
 Symbol s; *Left hand side of the equation.*
 Symbol t; *Right hand side of the equation.*
 Put an equation s=t onto the heap of a record. If a field s is already there then the value is overwritten. The arguments are expected to be symbols. Thus it is not necessary to make private copies and it is possible to avoid expensive string comparisons.
 Returns: nothing
- Record record_gc()** Function
 Record rec; *Pointer to any entry in the chain.*
 Garbage collecting a record list. The entries marked as deleted are unlinked and the memory is freed. Any pointer to such a deleted entry becomes invalid.

Be careful when using this function!

Returns: Pointer to some entry in the cleared chain or `RecordNULL` if none is left.

Symbol `record_get()` Function

Record `rec`; *the record*
 Symbol `key`; *the key*

Returns:

void `sort_record()` Function

Record `rec`; *Record to sort*

The heap is reordered according to the sorting order determined by the record type. For this purpose a copy of the original record is made and the original record is overwritten. The copy is released at the end. Memory management is easy since all strings are in fact symbols, i.e. they must not be freed and comparison is done by pointer comparison.

Returns: nothing

Record `unlink_record()` Function

Record `rec`; *Record to free.*

Remove a record from a chain and free its memory. The chain is modified such that the freed Record is not referenced any more. A neighbor in the chain of the given record is returned or `NULL` if there is none.

Returns: nothing

2.28 The Header File `bibtool/rewrite.h`

2.29 The Module `rewrite.c`

void `add_check_rule()` Function

String `s`; *Rule to save.*

Save a check rule for later use.

Returns: nothing

void `add_extract()` Function

Symbol `s`; *Rule to save.*
 int `regexp`; *Boolean value indicating whether regular expressions should be used. If not set then plain string matching is performed.*
 int `notp`; *Boolean value indicating whether the result should be negated.*

Save an extraction rule for later use. The argument is interpreted as regular expression to be matched against the field value.

The value of `rsc_case_select` at the invocation of this function determines whether the matching is performed case sensitive or not.

Returns: nothing

`void add_field()` Function

String spec; *A string of the form token=value*

Save a token and value for addition.

Returns: nothing

`void add_rewrite_rule()` Function

String s; *Rule to save*

Save a rewrite rule for later use. The main task is performed by `add_rule()`.

Returns: nothing

`void clear_addlist()` Function

Reset the addlist to the empty list.

Returns: nothing

`bool foreach_addlist()` Function

bool (*fct) (Symbol key, Symbol val);

Returns:

`char* get_regex_syntax()` Function

Getter for the regex syntax.

Returns:

`bool is_selected()` Function

DB db; *Database containing the record.*

Record rec; *Record to look at.*

Boolean function to decide whether a record should be considered. These selections are described by a set of regular expressions which are applied. If none are given then the match simply succeeds.

Returns: `true` iff the record is selected by a regexp or none is given.

`void keep_field()` Function

Symbol spec; *the specification*

Returns: nothing

`void remove_field()` Function

Symbol field; *This is a symbol containing the name of the field to remove.*

Record rec; *Record in which the field should be removed.*

Remove the given field from record.

Returns: nothing

`void rename_field()` Function
 Symbol spec; *the argument*

Returns: nothing

`void rewrite_record()` Function
 DB db; *The database record is belonging to.*
 Record rec; *Actual record to apply things to.*
 Apply deletions, checks, additions, and rewriting steps in this order.
 Returns: nothing

`void save_regex()` Function
 String s; *Regular expression to search for.*
 Save an extraction rule for later use. Only the regular expression of the rule is given as argument. The fields are taken from the resource select.fields.
 Returns: nothing

`int set_regex_syntax()` Function
 char* name;
 experimental
 Returns: nothing

2.30 The Header File `bibtool/resource.h`

This file is the central component of the resource evaluator. To reduce redundancy everything in this file is encapsulated with macros. Thus it is possible to adapt the meaning according to the task to be performed.

This file is included several times from different places. One task is the definition of certain variables used in this file. Another task is the execution of the commands associated with a command name.

This is one place where the power and the beauty of the C preprocessor makes live easy. It should also be fun to figure out the three ways in which this file is used. Read the sources and enjoy it!

For the normal user this file is consulted automatically when the header file `rsc.h` is used.

2.31 The Header File `bibtool/rsc.h`

This header file provides definitions for all resource variables, i.e. the variables defined in the header file `resource.h`.

In addition the functions defined in `resource.c` are made accessible to those modules including this header file.

2.32 The Module `rsc.c`

This module contains functions which deal with resources. Resources are commands to configure the behaviour of BIBTOOL. They can be read either from a file or from a string.

The syntax of resources are modelled after the syntax rules for `BIBTEX` files. See the user's guide for details of the syntax.

`bool load_rsc()` Function

`String name;` *The name of the resource file to read.*

This function tries to load a resource file. Details: Perform initialization if required. The main job is done by `read_rsc()`. This function is located in `parse.c` since it shares subroutines with the parser.

Returns: `false` iff the reading failed.

`bool resource()` Function

`String name;` *the name of the resource file*

Returns:

`void rsc_print()` Function

`String s;` *String to print.*

Print a string to the error stream as defined in `error.h`. The string is automatically augmented by a trailing newline. This wrapper function is used for the resource print.

Returns: nothing

`bool search_rsc()` Function

Try to open the resource file at different places:

- In the place indicated by the environment variable `RSC_ENV_VAR`. This step is skipped if the macro `RSC_ENV_VAR` is not defined (at compile time of the module).
- In the home directory. The home directory is determined by an environment variable. The macro `HOME_ENV_VAR` contains the name of this environment variable. If this macro is not defined (at compile time of the module) then this step is skipped.

- In the usual place for resource files.

For each step `load_rsc()` is called until it succeeds.

The files sought is determined by the macro `DefaultResourceFile` at compile time of the module. (see `bibtool.h`)

Returns: `true` iff the resource loading succeeds somewhere.

```
bool set_rsc() Function
Symbol name; Name of the resource to set.
Symbol val; The new value of the resource.
```

Set the resource to a given value. Here the assignment is divided into two parts: the name and the value. Both arguments are assumed to be symbols.

Returns: `false` iff everything went right.

```
bool use_rsc() Function
String s; String containing a resource command.
```

This function can be used to evaluate a single resource instruction. The argument is a string which is parsed to extract the resource command.

This is an entry point for command line options which set resources.

Returns: `true` iff an error has occurred.

2.33 The Header File `bibtool/s_parse.h`

This string parser.

2.34 The Module `s_parse.c`

```
Symbol s_parse() Function
int type; is the type of construct to parse. It is defined in
s_parse.h
String *sp; is a pointer to the string which is parsed. The value is
changed to hold the remaining characters at the end.
bool errp; this boolean indicated whether or not a verbose error
message should be created in case of an error.
```

Parse a string for a certain entity. Leading whitespace is ignored. `type` determines which kind of entity should be expected. It can take the following values which are defined in `s_parse.h`:

StringParseValue The string is analyzed and the proper type is determined automatically. This can be considered as the normal way of operation.

StringParseSymbol The string is analyzed and only a symbol is accepted, i.e. a

sequence of allowed characters.

StringParseNumber The string is analyzed and only a number is accepted.

StringParseBraces The string is analyzed and only an expression in braces is accepted. The braced contained must come in matching pairs. The whole expression – including the braces – is returned.

StringParseUnquotedBraces The string is analyzed and only an expression in braces is accepted. The braced contained must come in matching pairs. The expression without the outer braces is returned.

StringParseString The string is analyzed and only a string enclosed in double quotes is accepted. The string must contain braces in matching pairs. Double quotes which are inside of braces are not considered as end of the string. The whole string – including the double quotes is returned.

StringParseUnquotedString The string is analyzed and only a string enclosed in double quotes is accepted. The string must contain braces in matching pairs. Double quotes which are inside of braces are not considered as end of the string. The string without the outer double quotes is returned.

If an error occurs or the requested entity is not found then `NULL` is returned. As a side effect `sp` is advanced to point to the next unprocessed character.

The string analyzed should be opened at the beginning with `sp_open()` in order to get an appropriate error message.

This function is usually not called directly but the convenience macros defined in `s_parse.h` should be used instead.

Returns: A symbol containing the requested entity or `NULL`.

`void sp_close()` Function

Release the string parser and rest it to its initial state.

Returns: nothing

`String sp_eos()` Function

`String *sp;` *the string pointer*

The string is analyzed and any remaining characters which are not whitespace are reported as error. A pointer to the terminating 0 byte

Returns:

`bool sp_expect()` Function

`String *sp;` *the pointer to the source string*

`String expect;` *the expected string*

`bool verbose;` *the indicator whether an error message should be produced*

Read a sequence of expected characters after whitespace. The source pointer is advanced until the expected string has been read or to the first character which is

not expected.

Returns: `true` iff the expected string is found

`void sp_open()` Function

`String s;` *String to open for parsing.*

Open a string for parsing. The argument string is used for the parsing process. Thus this string should not be modified during this time. Especially it should not be freed if it is a pointer to dynamically allocated memory.

Returns: nothing

`void sp_skip()` Function

`String *sp;` *the string pointer*

Advance a String pointer to the next character which is not a white-space, equals or hash.

Returns:

`Symbol* sp_symbols()` Function

`String *sp;` *the pointer to the value to be parsed*

Returns: an array of Symbols

2.35 The Header File `bibtool/stack.h`

This module provides access to the functions defined in the module `stack.c`. The the documentation of this module for details.

2.36 The Module `stack.c`

This module provides a single stack of strings. There are two operations on this stack, namely to push a string onto the stack and a pop operation to get the topmost element from the stack and remove it or to get a signal that the stack is empty.

The stack is implemented as an array which grows on demand. Currently the memory of the stack is not returned to the operating system. This seems to be not problematic since this memory is not assumed to be really large. Normally just a few strings are pushed to the stack at any time.

`Symbol pop_string()` Function

Pop a string from the stack. If the stack is empty then `NULL` is returned. Thus the `NULL` value should not be pushed to the stack since this can be confused with the end of the stack.

Returns: The old top element or `NULL` if the stack is empty.

void push_string() Function
 Symbol *s*; *String to push to the stack.*
 Push a string onto the stack. Only the memory for the stack is allocated. The string is stored as pointer to existing memory. No copy of the string is made.
 If no memory is left then an error is raised and the program is terminated.
 Returns: nothing

2.37 The Header File `bibtool/sbuffer.h`

This header file makes accessible the functions to treat strings like streams. In addition to the functions defined in `sbuffer.c` one macro is defined here.

sbputchar() Macro
 C *Character to put.*
 SB *Destination string buffer.*
 Put the character *C* into the string buffer *SB*.
 This macro is not sane. The arguments are expanded several times. Thus they must not contain side effects.
 Returns: nothing

2.38 The Module `sbuffer.c`

This module contains functions for dealing with strings of arbitrary size. The allocation of memory is done automatically when more characters are added.

The functions are modeled after the stream functions of C. Currently a `printf`-like function is missing because one was not needed yet and it is not so easy to implement—portably.

The functions in this module are very handy to deal with strings of arbitrary length where the length is not known in advance. E.g. consider the case that a line has to be read from a file `file` and the line length should not be restricted by some artificial boundary. This can be implemented as follows:

```
{ StringBuffer *sb = sb_open();      /* Declare and initialize a string buffer. */
  int c;                             /* Variable to store a single character. */
  char *s;                           /* Variable to hold the string at the end. */
  while ( (c=fgetc(file) != EOF
          && c != '\n')
  { sbputchar(c,sb); }               /* Store each character in the string buffer.
                                     */
  s = sbflush(sb);                  /* Get the string from the string buffer. */
  puts(s);                          /* Process the string; e.g. print it. */ }
```

[illegible]

<code>bool sbclose()</code>	Function
<code>StringBuffer* sb;</code>	<i>Pointer to string buffer which should be closed</i>
Free an old string buffer.	
Returns: Return <code>false</code> upon failure.	

`char* sbflush()` Function

`StringBuffer* sb;` *String buffer to close.*

Close a string buffer with a trailing `\0` and reset the current pointer to the beginning. The next write operation starts right at the end. Thus additional write operations will overwrite the terminating byte.

Returns: The string contained in the string buffer as a proper C string.

StringBuffer* sbopen()	Function
Allocate a new string buffer. Return a pointer to the new string buffer or NULL if none was available.	
Returns: pointer to new string buffer or NULL	

```

bool sbputc()
    int c;           Character to put to the string buffer.
    StringBuffer* sb; Destination string buffer.

```

Push a single character onto a string buffer. In contrast to the macro this function handles the reallocation of the memory. For the user it should not make a difference since the macros uses this function when needed.

When no memory is left then the character is discarded and this action is signaled via the return value.

Returns: `false` if no memory is left.

<code>bool sbputs()</code>		Function
<code>char * s;</code>	<i>String to be pushed.</i>	
<code>StringBuffer* sb;</code>	<i>Destination string buffer.</i>	
Push a whole string onto a string buffer.		
Returns: <code>false</code> if something went wrong.		

<code>void sbrewind()</code>	Function
<code>StringBuffer* sb;</code>	<i>String buffer to consider.</i>

Reset the string buffer pointer to the beginning. The next write or read will operate there.

Returns: nothing

```
bool sbseek() Function
StringBuffer* sb; String buffer to reposition.
int pos; New position of the string buffer.
```

Reset the current pointer to the position given. If the position is outside the valid region then `true` is returned and the position is left unchanged.

Returns: `false` if everything went right.

```
int sbtell() Function
StringBuffer* sb; String buffer to consider.
```

Return the current pointer to the string buffer position. This can be used with `sbseek()` to reset it.

Returns: The relative byte position of the current writing position. This is an integer offset from the beginning of the string buffer.

2.39 The Header File `bibtool/symbols.h`

This header file contains definitions dealing with symbols.

BIBTOOL uses symbols as the basic representation for strings. Symbols are stored in a symbol table and shared among different instances. Thus the same string occurring at different places has to be stored only once.

Another advantage of symbols is that once you have got two symbols at hand it is rather easy to compare them for equality. A simple pointer comparison is enough. It is not necessary to compare them character by character.

The disadvantage of a symbol is that you can not simply modify it temporarily since it is part of the symbol table. This symbol table would be in an insane state otherwise. Thus you always have to make a copy if you want to modify a symbol.

The functions defined in `symbols.c` are exported with this header file as well.

```
void UnlinkSymbol() Macro
SYM Symbol to release.
```

The symbol given as argument is released. In fact the memory is not really freed but one instance is marked as not used any more. At other places the symbol might be still required. The freeing of memory is performed by the garbage collector `sym_gc()`.

Returns: nothing

```
Symbol NO_SYMBOL Macro
```

The NULL pointer for Symbols

String <code>s_empty</code>	Variable
Unmodifiable value containing the empty string. This variable needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_empty</code>	Variable
The empty symbol. This is a symbol pointing immediately to a <code>\0</code> byte. This needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_crossref</code>	Variable
The symbol <code>crossref</code> . This variable needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_xref</code>	Variable
The symbol <code>xref</code> . This variable needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_xdata</code>	Variable
The symbol <code>xdata</code> . This variable needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_space</code>	Variable
The symbol with a single space character. This variable needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_comma</code>	Variable
The symbol with a single comma character. This variable needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_double_quote</code>	Variable
The symbol with a single double quote character (<code>"</code>). This variable needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_open_brace</code>	Variable
The symbol with a single open brace character. This variable needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_close_brace</code>	Variable
The symbol with a single close brace character. This variable needs <code>init_symbols()</code> to be called first.	
Symbol <code>sym_et</code>	Variable
The symbol with a single et character (<code>&</code>). This variable needs <code>init_symbols()</code> to be called first.	
String <code>newString()</code>	Macro
<code>S</code>	<i>the source of the bytes</i>
Create a copy of a given String.	
Returns: a newly allocated byte array containing the content of the source	

2.40 The Module `symbols.c`

This module contains functions which deal with symbols and general memory management. This module implements a single symbol table.

This module required initialization before all functions can be used. Especially the symbol table does not exist before initialization.

`SYM_PIPE_SIZE`

Macro

`void free_sym_array()`

Function

Symbol `*sym_arr`; *symbol array*

Returns: nothing

`void init_symbols()`

Function

Initialize the symbols module. The symbol table is cleared. This is not secure when the symbols have already been initialized because it would lead to a memory leak and a violation of the symbol comparison assumption. Thus this case is caught and nothing is done when the initialization seems to be requested for the second time.

If no more memory is available then an error is raised and the program is terminated.

Note that this function is for internal purposes only. The normal user should call `init_bibtool()` instead.

Returns: nothing

`char * new_string()`

Function

char `* s`; *String to duplicate*

Allocate a space for a string and copy the argument there. Note this is just a new copy of the memory not a symbol!

If no more memory is available then an error is raised and the program is terminated.

Returns: Pointer to newly allocated memory containing a duplicate of the argument string.

`void sym_del()`

Function

Symbol `sym`;

Returns: nothing

`void sym_dump()`

Function

Dump the symbol table to the error stream—see module `error.c`. The symbols are printed according to their hash value and the sequence they are occurring in the buckets. A summary of the memory used is also printed.

Returns: nothing

Symbol `sym_extract()` Function

String `*sp`; *pointer to the string*
 bool `lowercase`; *indicate that lowering is requested*

Extract a symbol from a string.

Returns:

void `sym_unlink()` Function

Symbol `sym`; *Symbol to be released.*

Free a symbol since it is no longer used. This does not mean that the memory is also freed. The symbol can be static or used at other places. The real free operation requires the garbage collector `sym_gc()` to be called.

If the argument is `NULL` or an arbitrary string (no symbol) then this case is also dealt with.

Returns: nothing

Symbol `symbol()` Function

String `s`; *String which should be translated into a symbol.*

Add a symbol to the global symbol table. If the string already has a symbol assigned to it then this symbol is returned. If the symbol is not static then the use count is incremented by `count`.

If the symbol does not exist already then a new symbol is added to the symbol table and the use count is initialized to `count`. A negative value for `count` indicates that a static symbol is requested. A static symbol will never be deleted from the symbol table. Static can be used at places where one does not care about the memory occupied.

If no more memory is available then an error is raised and the program is terminated.

See also the macro `symbol()` in `symbols.h` for a convenient alternative to this function.

Returns: The new symbol.

2.41 The Header File `bibtool/tex_aux.h`

2.42 The Module `tex_aux.c`

bool `apply_aux()` Function

DB `db`; *Database to clean.*

This function deletes all entries which are not requested by the recently read aux

file. This means that the entry to be kept is either mentioned directly, it is cross-referenced, or all entries are requested with the `\nocite{*}` feature.

Note that the entries are in fact not deleted but only marked as deleted. Thus they can be recovered if necessary.

Returns: `false` iff all entries are kept because of an explicit or implicit star (*).

`bool aux_used()` Function
`Symbol s;` *reference key to check*

Check whether a reference key has been requested by the previously read aux file. The request can either be explicit or implicit if a * is used.

Returns: `true` if the reference is used.

`void clear_aux()` Function
 Reset the aux table to the initial state.
 Returns: nothing

`bool foreach_aux()` Function
`bool (fct)(Symbol);` *function to apply*
 Apply the function to all words in the citation list of the aux file.
 Returns: `cite_star`

`bool read_aux()` Function
`String fname;` *The file name of the aux file.*
`void (*fct)(char*);` *A function to be called for each BIB_T_E_X file requested.*
`bool verbose;` *Boolean indicating whether messages should be produced indicating the status of the operation.*

Analyze an aux file. If additional files are requested, e.g. by `\include` instructions in the original source file then those are read as well. Each citation found is remembered and can be queried afterwards. If a `\cite{*}` has been used then only a flag is set and all citation keys are discarded.

The aux file contains also the information about the BIB_T_E_X files used. For each such file the function `fct` is called with the file name as argument. This function can arrange things that those BIB_T_E_X files are read into a database.

This function has only a very simple parser for the aux file. Thus it can be confused by legal contents. But a similar thing can happen to BIB_T_E_X as well.

Returns: `true` iff the file could not be opened.

2.43 The Header File `bibtool/tex_read.h`

This header file provides definitions for the use of functions to immitate the reading apparatus of `TEX` which are defined in `tex_read.c`.

2.44 The Module `tex_read.c`

This module contains functions which immitate the reading apparatus of `TeX`. Macro expansion can be performed.

```
void TeX_active() Function
    int    c; Character to make active.
    int    arity; Arity of the macro assigned to the active character.
    String s; Body of the definition as string.
    Assign a macro to an active character. If the character is not active then the
    catcode is changed.
    Returns: nothing
```

```
void TeX_close() Function
    Gracefully terminate the reading of TeX tokens. Any remaining pieces of text
    which have already been consumed are discarded.
    Returns: nothing
```

```
void TeX_def() Function
    String s;
    Define a macro. The argument is a string specification of the following form:
    \name[arity]=replacement text
    \name=replacement text
    0 <= arity <= 9
    Returns: nothing
```

```
void TeX_define() Function
    String name;
    int    arity;
    String body;
    Add a new TeX macro definition.
    Returns: nothing
```

```
void TeX_open_file() Function
    FILE * file; File pointer of the file to read from.
    Prepare things to parse from a file.
    Returns: nothing
```

```
void TeX_open_string() Function
    String s; String to read from.
    Prepare things to parse from a string.
    Returns: nothing
```

bool TeX_read() Function
 String cp; *Pointer to position where the character is stored.*
 String *sp; *Pointer to position where the string is stored.*
 Read a single Token and return it as a pair consisting of an ASCII code and possibly a string in case of a macro token.
 Returns: **false** iff everything went right.

void TeX_reset() Function
 Reset the T_EX reading apparatus to its initial state. All macros and active characters are cleared and the memory is released. Thus this function can also be used for this purpose.
 Returns: nothing

2.45 The Header File `bibtool/type.h`

This module is a replacement for the system header file `ctype.h`. In contrast to some implementations of the `isalpha` and friends the macros in this header are stable. This means that the argument is evaluated exactly once and each macro consists of exactly one C statement. Thus these macros can be used even at those places where only a single statement is allowed (conditionals without braces) or with arguments containing side effects.

In addition this is a starting point to implement an xord array like T_EX has one (some day...)

This header file requires the initialization function `init_type()` to be called before the macros will work as described.

This header file also provides the functions and variables defined in `type.c`

char* trans_lower Variable
 Translation table mapping upper case letters to lower case. Such a translation table can be used as argument to the regular expression functions.

char* trans_upper Variable
 Translation table mapping lower case letters to upper case. Such a translation table can be used as argument to the regular expression functions.

char* trans_id Variable
 Translation table performing no translation. Thus it implements the identity a translation table can be used as argument to the regular expression functions.

bool is_allowed() Macro
 C *Character to consider*
 Decide whether the character given as argument is an allowed character in the sense of BibT_EX.

Returns: TRUE iff the argument is an allowed character.

`bool is_upper()` Macro

`C` *Character to consider*

Decide whether the character given as argument is a upper case letter. (Characters outside the ASCII range are not considered letters yet)

Returns: TRUE iff the character is an uppercase letter.

`bool is_lower()` Macro

`C` *Character to consider*

Decide whether the character given as argument is a lower case letter. (Characters outside the ASCII range are not considered letters yet)

Returns: TRUE iff the character is a lowercase letter.

`bool is_alpha()` Macro

`C` *Character to consider*

Decide whether the character given as argument is a letter. (Characters outside the ASCII range are not considered letters yet)

Returns: TRUE iff the character is a letter.

`bool is_digit()` Macro

`C` *Character to consider*

Decide whether the character given as argument is a digit. (Characters outside the ASCII range are not considered letters yet)

Returns: TRUE iff the character is a digit.

`bool is_space()` Macro

`C` *Character to consider*

Decide whether the character given as argument is a space character. '`\0`' is not a space character.

Returns: TRUE iff the character is a space character.

`bool is_extended()` Macro

`C` *Character to consider*

Decide whether the character given as argument is an extended character outside the ASCII range.

Returns: TRUE iff the character is an extended character.

`bool is_wordsep()` Macro

`C` *Character to consider*

Decide whether the character given as argument is a word separator which denotes no word constituent.

Returns: TRUE iff the character is a word separator.

char ToLower() Macro
 C *Character to translate*

Translate a character to it's lower case dual. If the character is no upper case letter then the character is returned unchanged.

Returns: The lower case letter or the character itself.

char ToUpper() Macro
 C *Character to translate*

Translate a character to it's upper case dual. If the character is no lower case letter then the character is returned unchanged.

Returns: The upper case letter or the character itself.

2.46 The Module type.c

This file contains functions to support a separate treatment of character types. The normal functions and macros in `ctype.h` are replaced by those in `type.h`. This file contains an initialization function which is required for the macros in `type.h` to work properly.

See also the documentation of the header file `type.h` for further information.

void add_word_sep() Function
 String s; *the allowed word separator characters*
 Mark some characters as word separator.
 Returns: nothing

bool case_eq() Function
 String s; *First string to consider.*
 String t; *Second string to consider.*
 Compare two strings ignoring cases. If the strings are identical up to differences in case then this function returns **true**.
 Returns: **true** iff the strings are equal.

int cmp() Function
 String s; *the first string*
 String t; *the second string*
 Compare two strings.
 Returns:

void init_type() Function
 This is the initialization routine for this file. This has to be called before some

of the macros in `type.h` will work as described. It does no harm to call this initialization more than once. It just takes some time.

Note that this function is for internal purposes only. The normal user should call `init_bibtool()` instead.

Returns: nothing

String lower() Function
 String *s*; *string to convert*
 Function to translate all letters in a string to lower case.
 Returns: The converted string.

2.47 The Header File `bibtool/version.h`

2.48 The Module `version.c`

char * bibtool_version Variable
 This string variable contains the version number of BIBTOOL. Usually it is of the form *major.minor* where *major* and *minor* are the major and minor version numbers. In addition a post-fix like **alpha** or a patch level like **p1** can be present.

char * bibtool_year Variable
 This string variable contains the publication year for this version.

void show_version() Function
 Print the version number and a short copyright notice onto the error stream.
 Returns: nothing

2.49 The Header File `bibtool/wordlist.h`

WordList Type
 This data type represents a node in a list of strings. This list only provides a next pointer. and is pretty generic.

```
typedef struct wORDLIST {
    Symbol          wl_word; String value of this node.
    struct wORDLIST *wl_next; Pointer to the next node.
} SWordList, *WordList;
```

WordList WordNULL Macro
 This is the NULL value for a WordList. It terminates the list and represents the empty node.

String ThisWord() Macro
 WL *WordList to consider which is not WordNULL.*

This macro returns the string of a **WordList** node.

Returns: The word stored in this node.

WordList NextWord() Macro
 WL *WordList to consider which is not WordNULL.*

This macro returns the next **WordList** node of a given **WordList** if this is not **WordNULL**.

Returns: The next **WordList**.

2.50 The Module `wordlist.c`

This module contains functions which deal with lists of words. Those words are in fact simple strings. Thus this module provides a very general functionality, namely a list of strings and the associated methods.

void add_word() Function
 Symbol **sym**;
 WordList ***wlp**; *Pointer to a wordlist.*

Put a string into a word list. The string itself is *not* copied. Thus it is highly recommended to use symbols as words nevertheless this is not required as long as the string **s** persists as long as the word list exists.

The second argument is a pointer to a **WordList**. This destination is modified by adding a new node. The use of a pointer allows a uniform treatment of empty and not empty word lists.

If no memory is left then an error is raised and the program is terminated.

Returns: nothing

int delete_word() Function
 Symbol **sym**;
 WordList ***wlp**; *Pointer to the word list to modify.*
 void (* fct)(String); *Function to call to free the memory occupied by the word.*

Remove a word from a **WordList**. Only the first appearance of such a word is removed. If a word is found which contains the same string as **s** then the associated node is removed from the list and the function **fct** is called to free the memory of the string in the **WordList** node if the function is not **NULL**. In this case the function returns 0. Otherwise 1 is returned.

Returns: 0 if the word was not found. 1 otherwise.

bool find_word() Function

String s; *String to find.*
WordList wl; *Word list to search in.*

Look up a word in a word list. The comparison is done case insensitive.

Returns: false iff the word does not occur in the word list.

bool foreach_word() Function
WordList wl; *WordList to traverse.*
bool (* fct)(Symbol); *function to apply.*

Applies the given function `fct` to all elements in the `WordList` as long as the function does not return 0. Thus it can be used to search for a specified word – e.g. determined by matching against a template. Another application the the processing of all elements in the `WordList`. In this case `fct` must always return `true`.

Returns: return value of last function or `true`.

void free_words() Function
WordList *wlp; *Pointer to the WordList.*
void (* fct)(Symbol); *Function to be called to free the memory of the word itself. If it is NULL then no function is called.*

Release the memory allocated for a list of words. All nodes in the list are freed. The function `fct` is called to free the memory occupied by the string component if it is not `NULL`.

Returns: nothing

3 Creating and Using the BibTool C Library

3.1 Creating the BibTool C Library

Creating the BIBTOOL library should not be too hard. Mainly make BIBTOOL in the main directory according to the instructions given there. As a side effect various object files are created. These object files—except the one for main.c—have to be put into the library.

For UNIX this is prepared in the makefile. Usually an invocation of make should be enough:

```
make libbib.a
```

This invocation of make is in fact the same as the following two commands:

```
ar r libbib.a $OFILES
ranlib libbib.a
```

Here \$OFILES denotes the list of object files as described above. On some systems no ranlib program is present and needed. In this case the second command can be omitted.

For other operating systems I simply do not know how things work there. I would be grateful to receive descriptions what to do there.

3.2 Using the BibTool C Library

If you have written a program which uses the BIBTOOL C Library you have to include the library into the linking list. In addition the directory where the library can be found has to be specified. On UNIX this can be done with the compiler switches `-l` and `-L` respectively. Thus consider you have a program named `mybib.c` and you have created the object file `mybib.o` for it. The linking step can be performed with the following command:

```
cc mybib.o -L$DIR -lbib -o mybib
```

Here \$DIR denotes the path containing the file `libbib.a`. This path can be omitted if the library has been installed in a “standard” place like `/usr/lib`.

4 Coding Standards

Several tools are used for the development of BIBTOOL. Mostly they are home grown—maybe they will be replaced by some wider used tools some day. Among those tools are indentation routines for Emacs to format the comments contained in the source. There is also a Lisp function to generate the function prototypes contained in the header files and sometimes in the C files as well. And finally there is a Program to extract the documentation from the source files and generate a printable manual.

All those support programs rely on standards for coding. Some of those standards have been developed independantly but should be used for consistency. In the following sections these coding standards are described.

4.1 K&R-C vs. ANSI-C

BIBTOOL tries hard to be portable to wide variety of C systems. Thus it can not be assumed that an ANSI C compiler is at hand. As a consequence the function heads are written in the old style which is also tolerated by ANSI compliant compilers. This means that the argument types are given after the argument list.

Here it is essential that the arguments type declarations are given in the same order as the arguments of the function. Each type variable must have a new type declaration in a line by it's own. This feature is used by the program which extracts the function prototypes.

Those function heads are use to generate function prototypes which can be understood by ANSI-C compilers as well as by of K&R compilers. This is achieved by the old trick to introduce a macro which expands to nothing on the old compilers and to its aregument on ANSI compilers. This macro is defined appropriately according to the existence of the macro `__STDC__` which should indicate an ANSI compliant compiler.

Index

add_check_rule()	43
add_extract()	43
add_field()	44
add_format()	22
add_ignored_word()	23
add_rewrite_rule()	44
add_sort_format()	23
add_sort_order()	41
add_word()	62
add_word_sep()	60
apply_aux()	55
apply_fmt()	24
apply_modify()	9
aux_used()	56
BIBALIAS	13
BIBCOMMENT	13
BIBEOF	13
BIBINCLUDE	13
BIBMODIFY	13
BIBNOOP	13
BIBPREAMBLE	13
BIBSTRING	13
bibtoolversion	61
bibtoolyear	61
case_eq()	60
clear_addlist()	44
clear_aux()	56
clear_ignored_words()	24
ClearRecordDELETED()	39
ClearRecordMARK()	40
ClearRecordXREF()	39
cmp()	60
copy_record()	41
count_record()	41
db_count()	9
db_find()	9
db_forall()	9
db_insert()	9
db_mac_sort()	10
db_new_key()	10
db_rewind()	10
db_search()	10
db_sort()	10
db_string()	11
db_xref_undelete()	11
DBalias()	8
DBcomment()	8
DBinclude()	8
DBmodify()	8
DBnormal()	8
DBpreamble()	8
DBstring()	8
DebugPrint1()	18
DebugPrint2()	18
DebugPrint3()	19
DebugPrintF1()	19
DebugPrintF2()	19
DebugPrintF3()	19
def_entry_type()	14
def_field_type()	28
def_format_type()	24
def_macro()	28
delete_record()	11
delete_word()	62
dump_mac()	29
each_macro()	29
end_key_gen()	24
EntryName()	12
entrytype	12
Err()	17
ErrC()	17
ERROR	15
ERREXIT	15
ERRFILE	15
ERROR()	16
error()	20
ERROR2()	16
ERROR3()	16
ERROREXIT()	16
ERRPOINT	15
ErrPrint()	17
ErrPrintF()	17

ErrPrintF2()	17	look_macro()	30
ErrPrintF3()	17	lower()	61
ERRWARNING	15	MacroCount()	28
expand_rhs()	21	MacroName()	28
find_entry_type()	14	MacroNULL	28
find_word()	62	MacroValue()	28
FlushErr	18	main()	5
fmt_expand()	24	make_key()	25
foreach_addlist()	44	make_sort_key()	25
foreach_aux()	56	mark_key()	26
foreach_ignored_word()	24	name_format()	32
foreach_macro()	29	NameMid()	32
foreach_word()	63	NameNULL	31
fput_record()	34	NamePost()	32
free_1_record()	41	NamePre()	31
free_db()	11	NameStrip()	31
free_key_node()	24	NameTrim()	31
free_macro()	29	NameType()	31
free_record()	42	new_db()	11
free_sym_array()	54	new_macro()	30
free_words()	63	new_record()	42
get_base()	25	new_string()	54
get_entry_type()	14	new_wordlist()	42
get_field()	25	newString()	53
get_item()	29	NextMacro()	28
get_key()	30	NextName()	32
get_regex_syntax()	44	NextRecord()	40
get_separator()	25	NextWord()	62
get_symbol_type()	35	NoDB	7
init_bibttool()	22	NOSYMBOL	52
init_entries()	14	OUTOFMEMORY()	16
init_error()	20	parse_bib()	33
init_macros()	30	pop_string()	49
init_read()	33	pp_list_of_names()	32
init_symbols()	54	pp_one_name()	32
init_type()	60	PrevRecord()	40
is_selected()	44	print_db()	11
isallowed()	58	provide_to_record()	42
isalpha()	59	push_string()	50
isdigit()	59	push_to_record()	42
isextended()	59	put_record()	35
islower()	59	px_fopen()	37
IsNormalRecord()	14	px_s2p()	37
isspace()	59	pxfilename	37
IsSpecialRecord()	13	read_aux()	56
isupper()	59	read_db()	12
iswordsep()	59	read_rsc()	33
keep_field()	44	record_gc()	42
load_rsc()	46	record_get()	43

RecordComment()	41
RecordFlagDELETED	38
RecordFlagMARKED	38
RecordFlags()	38, 41
RecordFlagXREF	38
RecordHeap()	40
RecordIsDELETED()	39
RecordIsMARKED()	40
RecordIsXREF()	39
RecordNULL	38
RecordOldKey()	40
RecordSortkey()	40
RecordSource()	41
RecordType()	38
remove_field()	44
rename_field()	45
resource()	46
rewrite_record()	45
rsc_print()	46
s_parse()	47
save_key()	31
save_regex()	45
sbclose()	51
sbflush()	51
sbopen()	51
sbputc()	51
sbputchar()	50
sbputs()	51
sbrewind()	51
sbseek()	52
sbtell()	52
search_rsc()	46
see_bib()	34
seen()	34
sempty	53
set_base()	26
set_field()	26
set_name_format()	32
set_regex_syntax()	45
set_rsc()	47
set_rsc_path()	34
set_separator()	26
set_symbol_type()	36
SetRecordDELETED()	39
SetRecordMARK()	40
SetRecordXREF()	39
show_version()	61
sort_record()	43
sp_close()	48
sp_eos()	48
sp_expect()	48
sp_open()	49
sp_skip()	49
sp_symbols()	49
sput_record()	36
start_key_gen()	27
sym_del()	54
sym_dump()	54
sym_extract()	55
sym_unlink()	55
symbol()	55
synclosebrace	53
symcomma	53
syncrossref	53
syndoublequote	53
symempty	53
symet	53
symopenbrace	53
SYMPIPE_SIZE	54
symospace	53
symxdata	53
symxref	53
TeX_active()	57
TeX_close()	57
TeX_def()	57
TeX_define()	57
TeX_open_file()	57
TeX_open_string()	57
TeX_read()	58
TeX_reset()	58
ThisWord()	62
ToLower()	60
ToUpper()	60
transid	58
translower	58
transupper	58
unlink_record()	43
UnlinkSymbol()	52
use_rsc()	47
VerbosePrint1()	18
VerbosePrint2()	18
VerbosePrint3()	18
VerbosePrint4()	18
WARNING()	16
WARNING2()	16
WARNING3()	16
WordNULL	61